

## Product Profile

- Rugged metal frame and enclosure
- Field proven 3400 reliability
- Industrial gray metallic color
- Up to 10 times improved throughput compared to 3400
- IEEE 1284 Parallel port and Serial port standard
- Internal Ethernet adapter optional
- Free LabelShop™ label design and print software
- Industry leading InterDriver™ Windows driver included
- 200 or 400 dpi printhead option



### EasyCoder™ 3400e PRINTER

The EasyCoder 3400e is a versatile industrial strength printer based on the rugged, field-proven EasyCoder 3400. The attractive gray metallic color of the 3400e fits in industrial or office environments. The 3400e features up to 10 times faster printing throughput compared to the 3400, making it ideal for today's increasingly complex labels combining 2D bar codes, mixed fonts and graphics – no waiting for labels.

The 3400e continues to offer the legendary reliability of the 3400 print mechanism. The steel frame enclosure gives the 3400e a rugged platform to withstand harsh industrial environments. The attractive gray metallic enclosure is designed to mask dirt and grime for ease of maintenance.

The EasyCoder 3400e features dramatically improved label processing speed and printing throughput compared to the 3400 and the competition. The standard high-speed IEEE 1284 parallel port and enhanced serial port ensure fast host communications. The internal Ethernet adapter provides high throughput and network management without the complexity, space requirements and fragility of external print servers. A heavy-duty cutter with tray option is available on the 3400D or 3400e printers. And of course, the 3400e is fully backward compatible with 3400A/B/C/D printers.

It all adds up to a powerful printer that is designed and built to be the right solution for a large variety of industrial bar code applications.

**Applications**

General Purpose Industrial Direct Thermal/Thermal Transfer Printer. Prints high quality bar codes on pressure sensitive labels and tags.

**Model**

EasyCoder 3400e

**Physical Characteristics**

**Length:** 43.8 cm (17.25")

**Width:** 24.9 cm (9.8")

**Height:** 27.7 cm (10.9")

**Weight:** 15.8 kg (35 lbs.)

**Print Specifications**

**Element:** 0.125 mm (0.00492")

**Resolution:** 8 dots/mm (203 dpi);  
16 dots/mm (400 dpi)

**"X" Dimension:** 0.13 to 1.27 mm  
(5 to 50 mil)

**Max. Length:** Unlimited

**Max. Width:** 104 mm (4.1") 203 dpi;  
112mm (4.4") 406 dpi

**Speed:** 51, 77, 102, or 128 mm/sec  
(Select 2", 3", 4", 5", 6" or 8")

**Media Specifications**

**Roll:** 152 m (6000" linear)

**Width:** 19 to 114 mm (.75 to 4.50")

**Length:** 13 to 610 mm (0.5 to 24");  
fanfold 432 mm (17") max.

**Roll Dimensions:** 213 mm (8.38")

**Thickness:** .08 to .31 mm  
(0.003 to 0.012")

**Core Size:** 76 mm (3")

**Ribbon Specifications**

**Roll:** 152 m (6000" linear)

**Widths:** 51, 77, 104, 114 mm  
(2", 3", 4.1", 4.5")

**Fonts and Graphics**

21 resident bitmapped fonts (includes OCR-A and OCR-B), 3 resident outline fonts, supports user-defined fonts and graphics, supports True Type fonts

**Language**

IPL3™, Compressed Graphics, Globe™, Backward Compatibility with 86XX and IPL2™

**Connectivity**

- Serial interface standard
- IEEE 1284 Parallel Standard
- Internal Ethernet interface optional
- Internal IBM Twinax or Coax interface optional

**Software**

- LabelShop™ START label design and print software
- Intermec InterDriver™ standard Windows 3.x, 9x, NT 4.0/5.0, Windows 2000
- Intermec ActiveX® controls standard Windows 9x, NT 4.0/5.0,
- PrintSet™ printer configuration utility Windows 3.x, 9x, NT4.0/5.0
- NetPilot™ + Thin Wizard™ network configuration utility (with optional Ethernet) Windows 9x, Windows NT 4.0/5.0

**Character Sets**

- Bitmapped using PrintSet™: All single-byte codepage; All double byte codepage.
- Code page 850, French, German, ISO 256 character, Italian, Kanji/Katakana (optional), Norwegian/Danish, Spanish, Swedish/Finnish, Swiss, UK ASCII, USA ASCII

**Power Supply**

100, 115, 200 and 230 V AC ± 10%;  
50 Hz to 60 Hz

**Printer Operating Environment**

**Operating Temperature:** 4° to 40°C  
(40° to 104°F)

**Storage Temperature:** 0° to 70°C  
(32° to 120°F)

**Humidity:** 10 to 90% (non-condensing)

**Bar Code Symbolologies**

Code 2 of 5, Code 11, Code 39, Code 93, Code 128, Codabar, HIBC, Interleaved 2 of 5, Postnet, UPC/EAN, JIS-ITF

**2D:** Code One, Code 16K, Code 49, DataMatrix, MaxiCode, PDF417, QR Code, Micro PDF

**Standards Supported**

UPC/EAN Shipping Container; UCC/EAN 128 Serial Shipping Container; MH10.8 Shipping Label; AIAG (shipping parts label); LOGMARS; POSTNET; ISBT 128; GM1724

**Regulatory Approvals**

Complies with all FCC Part 15, Class A; CISPR 22 Class B; ICES-003 Class B; UL, CSA & TÜV-GS agency approved; CE, NOM & C-TIC

**Options**

Cutter/tray; internal Ethernet; Self-Strip and rewind; Twinax or Coax; DRAM image expansion 4 MB; Flash storage expansion 16 MB; Kanji/Katakana fonts

**North America**

Corporate Headquarters  
6001 36<sup>th</sup> Avenue West  
Everett, Washington 98203  
tel: 425.348.2600  
fax: 425.355.9551

**Systems & Solutions**

550 2<sup>nd</sup> Street S.E.  
Cedar Rapids, Iowa 52401  
tel: 319.369.3100  
fax: 319.369.3453

**Media Supplies**

9290 Le Saint Drive  
Fairfield, Ohio 45014  
tel: 513.874.5882  
fax: 513.874.8487

**Europe/  
Middle East & Africa**

Headquarters  
Sovereign House  
Vastern Road  
Reading, Berkshire RG1 8BT  
United Kingdom  
tel: +44.118.987.9400  
fax: +44.118.987.9401

**Gothenburg**

Idrottsvägen 10  
P.O. Box 123  
SE-431 22 Mölndal  
Sweden  
tel: +46.31.869500  
fax: +46.31.869595

**Asia/  
Latin America**

Hong Kong  
26-12 Shell Tower  
Times Square  
1 Matheson Street  
Causeway Bay  
Hong Kong  
tel: 852.2574.9777  
fax: 852.2574.9725

**Singapore**

25-16 International Plaza  
10 Anson Road, 079903  
tel: 65.324.8391  
fax: 65.324.8393

**Australia**

Level 7, 200 Pacific Highway  
Crows Nest NSW 2065  
Australia  
tel: 61.2.9901.2065  
fax: 61.2.9954.6300

**South America and Mexico**

2572 White Road  
Irvine, California 92614  
tel: 949.975.1905  
fax: 949.975.1913

**Worldwide**

**Fax Document Retrieval Service**  
800.755.5505  
(North America Only)  
tel: 650.556.8447

**Internet**

www.intermec.com

**Sales**

800.347.2636  
(toll free in N.A.)  
tel: 425.348.2726

**Service and Support**

800.755.5505  
(toll free in N.A.)  
tel: 425.356.1799

Copyright © 2001 Intermec Technologies Corporation. All rights reserved. Intermec is a registered trademark of Intermec Technologies Corporation. All other trademarks are the property of their respective owners. Printed in the U.S.A. 611049-01A 07/01

In a continuing effort to improve our products, Intermec Technologies Corporation reserves the right to change specifications and features without prior notice.