

DIRECT THERMAL/
THERMAL TRANSFER
PRINTER

EasyCoder™ E4

Benefits:

- **Versatile**, the EasyCoder E4 enhances productivity and is easy to use.
- **Designed with the operator in mind**: supplied with Connect and Print™ features, like LabelShop START™ software, label and ribbon rolls, Windows™ driver, and parallel computer connection cable.
- **Robust Feature Set** allows the user to address multiple applications.
- **Compact**, the EasyCoder E4 will virtually fit anywhere.
- **Easy to load ribbons and labels**, reduces down time and increases productivity.
- **RS232 and Centronics® Parallel Connections** are standard features.
- **Peel off function with Label-Taken sensor for internal rewind of backing paper is also standard.**
- **The EasyCoder E4 printer is now also available in a LinerLess version.**



The EasyCoder E4 provides a reliable thermal transfer and direct thermal printing solution in numerous environments. Compact in design, the EasyCoder E4 printer is ideal where space is limited and performance is required.

The EasyCoder E4 is packed with features that would normally be considered options with other printers in the same class. For quick and easy printing, the printer is supplied with Intermec's Connect and Print™ features: LabelShop START Label Design & Print software, InterDriver™ with ActiveX™ controls Windows™ driver, parallel computer connection cable, and sample roll of labels and ribbon.

The EasyCoder E4 comes standard with 1MB of FLASH memory, two PC card slots, internal rewinder, Label-Taken Sensor, plus RS232 and Centronics Parallel connections.

Unicode TrueType™ fonts support is standard with the EasyCoder E4. In fact, 15 scaleable fonts are included, and more fonts in local languages—including Latin and non-Latin—can be downloaded into flash memory or be supported using a PC card.

Intermec's unique EasySet System is standard with the EasyCoder E4. The system incorporates a bar code interface allowing quick and effortless set-up of media and ribbon parameters, for precise and secured print quality.

The printer is designed on a chassis of reinforced composite materials, and covers consist of Polycarbonate and ABS plastics. These materials are all non-hazardous and recyclable, which also makes the EasyCoder E4 environment friendly.

EasyCoder™ E4

General

Direct Thermal and Thermal Transfer printer for labels, tickets and tags. Peel-off function with Label-Taken Sensor, plus internal rewind of backing paper. Separate LinerLess version for Direct Thermal labels.

Models

EasyCoder E4
EasyCoder E4 LinerLess

Physical Characteristics

Length: 350 mm (13.8")
Height: 170 mm (6.7")
Width: 236 mm (9.3")
Weight: 4.7 kg (10.4 lbs)

Print Specifications

Print Width:
Max. 104 mm (4.09")
Print Speed:
Max. 150 mm/s (6 in/s)
Print Direction:
Prints text, bar codes, and crisp graphics in all four directions.
Print Resolution:
203 dpi (8 dots/mm)

Media Specifications

Label Size –
Max. width: 114 mm (4.5")
Min. length: 10 mm (0.4")
Max. length: unlimited
Label/Ribbon Roll –
Label roll: max. diam. 150 mm (6")
=approx. 100 m of labels (4000")
Ribbon roll: max. diam. 60 mm (2.3")
=approx. 200 m of ribbon (8000")
Media core: 38-40 mm (1.5"-1.6")
or 3" (75 mm)
Media/Ribbon Characteristics –
Style: Roll-fed, die-cut, continuous, or fanfold labels, tags or tickets, or LinerLess labels
Type: Plain paper thermal transfer or thermal sensitive papers
Ribbon type: wax, wax/resin, resin

Paper and Ribbon Set-up

EasySet System–built-in bar code wand interface offers instant printer setting for various papers, ribbons and other printer parameters.

Connect and Print™

Intermec's Connect and Print™ package contains: LabelShop START Label Design & Print software, InterDriver™ with ActiveX™ controls Windows™ driver, parallel computer connection cable, and sample roll of labels and ribbon.

Software

Printer language: Intermec Direct Protocol.
Shipped with InterDriver™ Windows printer driver for Windows 3.11, Windows 95, 98 & NT to be used with standard Windows applications, such as Word, Access etc.
Also compatible with Windows label design packages, such as Intermec LabelShop and a wide range of software from independent software vendors.

Characters/Fonts

15 scaleable Unicode TrueType™ fonts:
Swiss 721 BT, Prestige 12 Pitch Bold BT, Zurich Extra Condensed BT, Swiss 721 Bold BT, Dutch 801 Roman BT, Swiss 721 Bold Condensed BT, Dutch 801 Bold BT, Century Schoolbook BT, Futura Light BT, Letter Gothic 12 Pitch BT, Mono-space 821 BT, Monospace 821 Bold BT, OCR-A BT, OCR-B 10 Pitch BT, and Zapf Dingbats BT.
Text can be smoothly printed at any size. Optional TrueType fonts on PC card for Eastern Europe, Middle East and Asia (Chinese, Japanese, Korean), Latin and non-Latin characters.

Bar Code Symbolologies

Incorporates 38 bar code symbolologies, including 2-Dimensional codes like Maxicode and PDF417.

Environment

+5° to +40°C (+40° to +104°F)

Humidity

20-80% RH non condensing

Power Supply

115 or 230V AC (+10%, -15%), 50 or 60 Hz

Memory

Standard: 1MB FLASH; 512KB DRAM; 2 PC card slots

Interface

Standard: RS232, Centronics® parallel
Baud Rate: 300-38400

Operator Control

1 three-coloured LED indicator lamp and 1 Print/Feed key

Regulatory Approvals

CE (EN55022 Class A), FCC Class A, UL, CSA, C-Tick

Options

Real Time Clock, Cutter for tickets and tags (not for linerless material), QR bar code, RS232 cable.

Where Information Gets Down To Business™

North America • 6001 36th Avenue West • P.O. Box 4280 • Everett, Washington 98203-9280 • 1 (800) 347-2636 tel • 1 (319) 369-3324 fax • Norand Mobile Systems Division • 550 2nd Street S.E. • Cedar Rapids, Iowa 52401 • 1 (800) 452-2757 tel • 1 (319) 369-3453 fax • Label Products: 1 (800) 227-9947 tel • 1 (513) 874-8487 fax

Europe/Middle East/Africa • Headquarters • Sovereign House • Vastern Road • Reading, RG1 8BT • United Kingdom • +44-118-987-9400 tel • +44-118-987-9401 fax • **France** • +33-1-30-15-25-35 tel • +33-1-34-80-14-33 fax • **Germany** • +49-211-536010 tel • +49-211-5360150 fax • **Italy** • +39-02-662-405 tel • +39-02-662-40558 fax • **Nordic Countries • Sweden** • +46 8 622 06 60 tel • +46 8 622 06 61 fax • **Denmark** • +45 48 166 166 tel • +45 48 166 167 fax • **Norway** • +47 67 91 17 10 tel • +47 67 91 17 11 fax • **Finland** • +358 9 52 37 21 tel • +358 9 52 92 24 fax • **Spain** • +34-91-383-2252 tel • +34-91-383-2247 fax • **United Kingdom** • +44-118-923-0800 tel • +44-118-923-0801 fax
For all other countries in Europe, Middle East, and Africa, Intermec Technologies Corporation has sales and service partners. For more information on a partner near you, please contact our European Headquarters listed above.

Asia Pacific/Latin America • 6001 36th Avenue West • P.O. Box 4280 • Everett, Washington 98203-9280 • 1 (800) 347-2636 tel • 1 (319) 369-3324 fax • Label Products: 1 (800) 227-9947 tel • 1 (513) 874-8487 fax

World-Wide Fax Document Retrieval Service • 1 (650) 637-2603 tel • 1 (800) 755-5505 (North America Only)

Internet • www.intermec.com **E-mail** • info@intermec.com

Copyright © 2000 Intermec Technologies Corp. All rights reserved. All trademarks are the property of their respective owners. Contents subject to change. 00.01