

QuickScan® QS1000

Handheld Scanner



Ideal for:

- Handheld or On-counter Mounting
- Area registers and at the front-end checkout
- Anywhere you need laser performance at an affordable price

Features

- Sleek, Triggerless Design Using LaserSense™ Technology
- Optimized for use in a stand
- Bright Light Scanning You Can Count On
- Unbeatable Price / Performance Ratio

Sleek Design and Powerful Performance. A Winning Combination in an Affordable Bar Code Scanner.

Step Up to the Performance of a Laser Scanner

The QuickScan® QS1000 scanner offers you all the benefits of laser scanning at what used to be CCD prices. The triggerless design, snappy scanning, and optional "hands-free" stand, give you enhanced performance at the point-of-sale — performance rarely found at such an affordable price.

The QS1000 consistently delivers speed and flexibility whether used at the point-of-sale checkout or for office, service or medical applications. And, it has an incredibly fast "speed-to-read" rate compared to other scanners in its class. When you're weighing price vs. performance, you don't need to look any further than the QS1000 scanner. The performance to price ratio is unparalleled, and the design is truly unique.

Innovative and Intelligent Design

The QS1000 was built to be handled... a lot. Providing user comfort "from the hand to the stand," and back again, was the primary consideration in its external design. The triggerless function and ergonomic design provide a sleek, attractive scanner that is as easy to use as it is comfortable.

The QS1000 is built smart on the inside too. A beryllium copper scan element provides incredibly high durability. And anti-shock mounts that can absorb up to 1,500 Gs protect the reading engine and optics. In even the toughest environments, you can rely on the QS1000 to keep right on performing—even with repeated 5.0' / 1.5 m drops to concrete.

The QuickScan 1000 Talks Your Language

With remarkable connectivity, the QS1000 supports all popular POS interfaces and keyboard wedges. And the QS1000 autodiscriminates all major bar code symbologies, and fully supports the UPC/EAN family of add-ons and code extensions.

The optional high visibility (650 nm) laser diode gives the QS1000 superior reading capabilities in bright light conditions. And advanced signal processing provides exceptional performance even on low contrast bar codes.

Get Laser Scanning Performance at a Price that will Surprise You

The QS1000 means you don't need to compromise. Get the laser scanning performance you've been looking for at a price you can afford. One look will tell you this is no ordinary scanner.



Specifications

QS1000

These product Specifications are subject to change without notice. Additional information concerning this product or other PSC products and services can be found at the PSC website: www.pscnet.com or contact your PSC representative for more information.

Specifications apply to RS232 interface with 680nm VLD unless otherwise stated.

Mechanical

Dimensions: 8.60 x 2.67 x 2.08" /
21.84 x 6.78 x 5.28 cm

Weight

Body (w/o cable): 6.2 ozs. / 176 g
Cable: 4.4 ozs. / 120 g

Cable length options

Collapsed: 20" / 51 cm, Extended: 8.0' / 2.4 m;
Collapsed: 81" / 206 cm, Extended: 11.5' / 3.5 m
(For other cable options, contact your PSC sales representative.)

Optical

Light source: Visible Laser Diode (VLD),
680 nm (nominal) & 650 nm (optional)
Scan system: Electromagnetic dithering mirror
Rate: 42 scans/sec. (nominal)
Depth-of-field: Refer to chart on this page
Resolution: 5 mils (0.13mm)
Print contrast ratio: 30% minimum
Pitch: ±65°
Skew: ±55°
Scan angle: 46°
Ambient light immunity:
Artificial light: 1,200 foot candles / 12912 Lux
Sunlight: 8,000 foot candles / 86080 Lux

Electrical

Operating voltage

Specifications using the 680nm laser diode & cable
Uncoded: 4.2 V to 14 VDC
Decoded: 3.8 V to 20 VDC

Operating current – nominal
Uncoded: 100mA @ 5 VDC
Decoded: 120mA @ 5 VDC

Idling current – nominal
Uncoded: 70mA @ 5 VDC
Decoded: 110mA @ 5 VDC

Environmental

Temperature rating

Operating: 32° to 122° F / 0° to 50° C
Storage: -40° to 158° F / -40° to 70° C

Humidity:

5 to 95% NC
Shock (at 23°C): withstands multiple 5.0' / 1.5 m
drops onto concrete / 100+ drops to countertop

Vibration: Operates in all normal retail and
office environments

Water & Dust: Resistant, IEC529 rating IP53DW

Decoding Capability

- UPC A, E / EAN 8,13 / JAN 8,13
(P2 / P5, Code 128 EAN add-ons
(interface dependent))
- Code 128/EAN 128
- Code 39
- Interleaved 2 of 5
- Codabar
- Code 93
- Pharmacode 39
- Standard 2 of 5, IATA

Communications

- RS232 and Keyboard Wedge
- Keyboard Wedge and Wand Emulation
- IBM 46xx and RS232
- Uncoded
- Universal Wedge
- OCIA and RS232

Safety & Regulatory

Electrical: Complies to Gost R; TÜV; UL; cUL
Emissions: Complies to FCC-A; EN 55022-B
BCIQ CNS13438; AS/NZS 3548; VCCI-B
Laser classification: CDRH Class II;
(CAUTION: Laser Radiation –
do not stare into beam);
IEC 60825 Class 2



Depth-of-Field Chart –

(printing resolution, contrast and ambient light dependent)

Label Density	Range	
5 mil	0.5" to 2.8" / 13 to 7.0 cm	
7.5 mil	0.0" to 4.5" / 0.0 to 11.4 cm	
10 mil	0.0" to 8.5" / 0.0 to 21.6 cm	
13 mil	0.0" to 11.5" / 0.0 to 29.2 cm	
20 mil	0.0" to 16.3" / 0.0 to 41.4 cm	

Available Mount Options



P/N: 7-0446
Stand
(included w/scanner)

P/N: 7-0622
Gooseneck Flexible
(flat)



QS1000

PSC Inc.

959 Terry Street
Eugene OR 97402-9150 USA
Tel: 800 695 5700 or 541 683 5700
Fax: 541 345 7140

PSC Worldwide Sales and Service locations

Australia Tel: 61 2 9878 8999 Fax: 61 2 9878 8688	Belgium Tel: 32 2 414 74 09 Fax: 32 2 410 11 63	Brazil Tel: 55 11 5507 7721 Fax: 55 11 5507 7696	Chile Tel: 562-339-7000 Fax: 562-339-7985	China Tel: 86 10 6857 9048 Fax: 86 10 6857 8699	China - South Tel: 86 20 8765 9955 Fax: 86 20 8765 9955	France Tel: 33 1 64 86 71 00 Fax: 33 1 64 46 72 44	Germany Tel: 49 6151 93580 Fax: 49 6151 935858
Hong Kong Tel: 852 25846210 Fax: 852 25210291	India Tel: 91 11 4621586 Fax: 91 11 4623305	Italy Tel: 39 039 629031 Fax: 39 039 6859496	Japan Tel: 81 3 3491 6761 Fax: 81 3 3491 6656	Latin America Tel: 1 305 539 0111 Fax: 1 305 539 0206	Singapore Tel: 65 435 1311 Fax: 65 226 1242	Spain Tel: 34 91 203 65 00 Fax: 34 91 203 65 01	Sweden Tel: 46 4010 84 92 Fax: 46 4010 84 91
Turkey Tel: 90 212 23691 15 Fax: 90 212 23691 16	United Kingdom Tel: 44 1923 809500 Fax: 44 1923 809505						

