

QuickScan® QS3500 & QS3000

Handheld Laser Scanners



Ideal for:

- All in-store applications
 - POS
 - Area Registers
 - Inventory
- Office and medical applications

Features:

- Reads Reduced Space Symbology (RSS)
- Ergonomic design
- Multiple Interfaces in one scanner
- Large bright LED and beeper with adjustable volume
- Two configurations – triggered and triggerless
- Five-year factory warranty

Ergonomic and Innovative Design Combined with Value and Performance.

The QuickScan® QS3500 and QS3000 Handheld Laser Scanners offer powerful scanning in an ergonomic and innovative design. With a large, bright LED window and adjustable beeper, the QS3500 and QS3000 ensure fast user feedback. Both models read RSS bar codes and are GTIN ready. The QS3500 and QS3000 will meet the needs of users requiring affordable performance and value in point-of-sale, medical, and light industrial applications.

Backed by a five-year warranty, the QS3500 and QS3000 provide excellent durability and reliability. With a five-foot drop specification and wide operating temperature range, the QS3500 and QS3000 will perform well in a variety of applications.

The QuickScan® QS3500

The QS3500 is a triggered handheld scanner, available in decoded and undecoded versions. With multiple interfaces (RS232, Keyboard Wedge, Wand Emulation, IBM 46XX and USB) on board, you will be able to connect easily to a variety of PCs and terminals. You'll also be able to configure your scanner to your particular needs with Advanced Data Formatting. And with flash memory, you'll be able to upgrade your scanner with the latest product updates.

The QuickScan® QS3000

The QS3000 is a triggerless version of the QS3500. It features the same multiple interfaces built-in, along with Advanced Data Formatting and flash memory. The QS3000 is available only in a decoded model. An optional hands-free stand allows you to have both a counter top and a handheld scanner.

Get Laser Scanning at an Affordable Price

The QS3500 and QS3000 are members of the QuickScan® family of value-priced scanners. All QuickScans provide superior performance, with advanced ergonomic design and enhanced durability, adding up to one of the best values in the industry.



Specifications

QuickScan® QS3500 & QS3000

These product Specifications are subject to change without notice. Additional information concerning this product or other PSC products and services can be found at the PSC website: www.pscnet.com or contact your PSC representative for more information.

Mechanical

Dimensions: 5.3 x 2.2 x 2.5" (13.4 x 5.7 x 6.4 cm)

Weight: 4.2 oz. (120 g) without cable

Cable: Removable 6.0' (1.8 m) – straight

(For other cable options, contact your PSC sales representative.)

Optical

Light source: 650 nm Visible Laser Diode (VLD)

Scan system: Bi-directional, Retrocollective

Rate: 50 ±6 scans/sec.

Depth-of-field: Refer to chart below

Resolution: 5 mils (0.13mm)

Print contrast: 30% minimum reflective difference

Pitch: ±65°

Skew: ±55°

Ambient light immunity

Artificial light: 450 foot candles (4,844 Lux)

Sunlight: 8,000 foot candles (86,112 Lux)

Electrical

Operating voltage

QS3500 Undecoded: 4.75 V to 14 VDC

QS3500 & QS3000 Decoded: 5 VDC ±10%

Operating current - nominal

QS3500 Undecoded: 100 mA at 5 VDC

QS3500 & QS3000 Decoded: 120 mA maximum

Power Sources:

QS3500 Undecoded: Power supplied by interface controller

QS3500 & QS3000 Decoded: Host power, or external power supply

Environmental

Temperature

Operating: 32° to 104° F (0° to 40° C)

Storage: -40° to 140° F (-40° to 60° C)

Humidity: 5 to 95% NC

Shock (at 23°C): Withstands multiple 5.0' (1.5 m) drops onto concrete

Decoding Capability

QS3500 & QS3000 Decoded:

- UPC A, E / EAN 8,13 / JAN 8,13 (with supplementals)

- UCC/EAN 128
- Code 39
- Code 39 Full ASCII
- Code 39 Trioptic
- Pharmacode 39
- Code 128
- ISBT 128
- Codabar
- Interleaved 2 of 5
- Discrete 2 of 5
- Code 93
- Code 11
- MSI/Plessey
- RSS-14 Standard
- RSS-14 Stacked
- RSS-14 Limited
- RSS-14 Expanded

QS3500 Undecoded:

- Determined by host

Communications

QS3500 & QS3000 / Decoded:

- RS-232
- Keyboard Wedge
- Wand Emulation
- IBM 468X/469X
- USB
- Synapse

QS3500 / Undecoded:

- Determined by interface controller

Safety & Regulatory

Electrical: Certified to UL1950, CSA C22.2 No. 1950, EN60950/IEC60950

Emissions: FCC part 15 Class A, ICES-0003 Class B, European Union EMC Directive, AS/NZS 3548 (Australia/New Zealand)

Laser classification:

CDRH Class II (QS3500 & QS3000);

IEC Class 2 (QS3500); IEC Class 1 (QS3000)



(ATTENTION: Laser Light - do not stare into beam)

Depth-of-Field — Printing resolution, contrast and ambient light dependent

Label Density	QuickScan® QS3500 Range	QuickScan® QS3000 Range
5 mils	0.0 to 2.0" / 0.0 to 5.1 cm	0.0 to 2.0" / 0.0 to 5.1 cm
7.5 mils	0.0 to 5.0" / 0.0 to 12.7 cm	0.0 to 4.0" / 0.0 to 10.2 cm
10 mils	0.0 to 7.0" / 0.0 to 17.8 cm	0.0 to 6.0" / 0.0 to 15.2 cm
13 mils	0.0 to 9.0" / 0.0 to 22.9 cm	0.0 to 8.0" / 0.0 to 20.3 cm
20mils	2.0 to 15.0" / 5.1 to 38.1 cm	0.5 to 11.0" / 1.3 to 27.9 cm



QS3X00 Stand



These products are manufactured in the United States and Singapore.

PSC Inc.

959 Terry Street
Eugene OR 97402-9150 USA
Tel: 800 695 5700 or 541 683 5700
Fax: 541 345 7140

PSC Worldwide Sales and Service locations

Australia Tel: 61 2 9878 8999 Fax: 61 2 9878 8688
Belgium Tel: 32 2 414 74 09 Fax: 32 2 410 11 63

Brazil Tel: 55 11 5507 7721 Fax: 55 11 5507 7696

Chile Tel: 562-339-7003 Fax: 562-946-1685

China Tel: 86 10 6857 9048 Fax: 86 10 6857 8699

China - South Tel: 86 20 8765 9955 Fax: 86 20 8765 9955

France Tel: 33 1 64 86 71 00 Fax: 33 1 64 46 72 44

Germany Tel: 49 6151 93580 Fax: 49 6151 935858

Hong Kong Tel: 852 25846210 Fax: 852 25210291
India Tel: 91 11 464 1662 Fax: 91 11 464 1662

Italy Tel: 39 039 629031 Fax: 39 039 6859496

Japan Tel: 81 3 3491 6761 Fax: 81 3 3491 6656

Latin America Tel: 1 305 539 0111 Fax: 1 305 539 0206

Singapore Tel: 65 435 1311 Fax: 65 226 1242

Spain Tel: 34 91 203 65 00 Fax: 34 91 203 65 01

Sweden Tel: 46 4010 84 92 Fax: 46 4010 84 91

Turkey Tel: 90 212 23691 15 Fax: 90 212 23691 16
United Kingdom Tel: 44 1923 809500 Fax: 44 1923 809505

